

# Rockstar<sup>TM</sup>



## WALL PRIMER

**INTERIOR**



**EXTERIOR**



*For Even Smooth Finishing*

# Rockstar - Primer ( Interior | Exterior )

**Rockstar™ Primer** the superior choice for wall priming. This water-thinnable, water-based acrylic wall liquid primer offers enhanced adhesion, maximum coverage, and long-lasting protection. Its exceptional opacity and whiteness bring out the true colors of your wall paint like never before. Say goodbye to peeling and hello to a flawless finish.

## KEY FEATURES & BENEFITS

- Excellent opacity and whiteness
- Improves appearance of top coat
- Does not chalk and can be applied on adequately cured fresh plaster
- Provides excellent adhesion to top coat emulsions

## INTERIOR

- For all surfaces like interior cement plasters, ceilings, and wall putty surfaces.

## SURFACE PREPARATION

- Sand the surface with emery paper no. 180 and ensure it is clean.
- Mix the primer with water in a 1:1 ratio. Apply a single coat using a brush or roller, and let it dry for 3-4 hours.
- To achieve a smooth surface, apply two coats of Wall Putty. After each coat, allow it to dry for approximately 10-12 hours. Once dried, use emery paper with a grit size of 320 to sand the surface, ensuring it is smooth and ready for further treatment or painting.
- Apply a second coat of Primer and let it dry for 3-4 hours. If needed, sand with emery paper no. 320. Then, apply the topcoat.

## EXTERIOR

- for all types of surfaces like exterior cement plasters, exterior ceilings, asbestos sheet, concrete, etc.

## SURFACE PREPARATION

- Ensure a clean surface, free from loose paint, dust, grease, fungi, etc.
- Smooth out surface imperfections like holes, dents, and cracks using Rockstar Wall Putty.
- Mix the primer with water in a 1:1 ratio.
- Apply a single coat of primer using a brush or roller and let it dry for 3-4 hours. Once the primer is dry, proceed to apply the topcoat for a beautiful and finished look.

## TECHNICAL INFORMATION

No.	Name of test	Result / Observations	No.	Name of test	Result / Observations
1.	Drying Time (surface Dry)	30 minutes	5.	Application Method	Spray, Brush or roller.
2.	Stability Of Thinned Paint	use within 24 hrs	6.	Shade Range	White Shade
3.	Thinning	100% by volume with water	7.	Safety Features	Non-Flammable.
4.	Overcoatability (drying Time To Recoat)	4 - 6 HRS @27° +/- 2°C & RH 60 ± 5%	8.	Post Application Instructions	Apply finishing coat within 7-8 days of primer application
			9.	Recommended Thinner	Water

## COVERAGE :

- INTERIOR - 16-19 sq.m/Ltr/ Coat | EXTERIOR - 10-13 sq.m/Ltr/ Coat

## PACKAGING, SHELF LIFE & STORAGE

- Available in 1L, 4L, 10L & 20L Bucket.
- 1 Year from the date of manufacturing
- keep in original tightly closed containers away from direct sunlight and excessive heat.